

## Coast Guard, DHS

## § 153.234

(3) Approved by the Commandant (GMSO).

[CGD 78-128, 47 FR 21207, May 17, 1982, as amended by CGD 82-063b, 48 FR 4782, Feb. 3, 1983]

### CARGO CONTAINMENT SYSTEMS

#### § 153.230 Type I system.

A type I containment system must meet the following requirements:

(a) The vessel must meet the requirements in subpart F of part 172 of this chapter for a type I hull.

(b) Except as described in § 153.235:

(1) It may be no closer to the tankship's shell than 76 cm (approx. 29.9 in.); and

(2) It may not be located in any part of the tankship subject to the damage described in Table 172.135 of this chapter for:

(i) COLLISION PENETRATION, Transverse extent; and

(ii) GROUNDING PENETRATION, Vertical extents from the baseline upward.

[CGD 73-96, 42 FR 49027, Sept. 26, 1977, as amended by CGD 79-023, 48 FR 51009, Nov. 4, 1983]

#### § 153.231 Type II system.

A type II containment system must meet the following requirements:

(a) The vessel must meet the requirements in subpart F of part 172 of this chapter for a type I or II hull.

(b) Except as allowed in §§ 153.7 and 153.235—

(1) It may be no closer to the tankship's shell than 76 cm (approx. 29.9 in.); and

(2) It may not be located in any part of the tankship subject to the damage described in Table 172.135 of this chapter for GROUNDING PENETRATION, Vertical extent from the baseline upward.

[CGD 73-96, 42 FR 49027, Sept. 26, 1977, as amended by CGD 79-023, 48 FR 51009, Nov. 4, 1983; CGD 81-101, 52 FR 7781, Mar. 12, 1987]

#### § 153.232 Type III system.

A type III containment system must be in either a type I, II, or III hull. The requirements for type I, II, and III

hulls are in subpart F of part 172 of this chapter.

[CGD 79-023, 48 FR 51009, Nov. 4, 1983]

#### § 153.233 Separation of tanks from machinery, service and other spaces.

(a) To prevent leakage through a single weld failure, the following spaces must be separated from a cargo by two walls, two bulkheads, or a bulkhead and a deck not meeting in a cruciform joint:

(1) Machinery spaces.

(2) Service spaces.

(3) Accommodation spaces.

(4) Spaces for storing potable domestic, or feed water.

(5) Spaces for storing edibles.

(b) Some examples of arrangements that may separate cargo from the spaces listed in paragraph (a) of this section are the following:

(1) Dedicated ballast tanks.

(2) Cargo pumprooms.

(3) Ballast pumprooms.

(4) Tanks not carrying a cargo listed in this part.<sup>3</sup>

(5) A cofferdam aft of the cargo containment systems and whose forward bulkhead is forward of any joint common to an accommodations space and the deck.

(6) Double walled piping or a piping tunnel.

#### § 153.234 Fore and aft location.

Except as allowed in § 153.7, each ship must meet the following:

(a) Each cargo containment system and any compartments within which a containment system is located must be forward of a tankship's accommodation spaces.

(b) Except as described in § 153.235, each cargo containment system must be located at least 0.05L aft of the forward perpendicular, but in no case forward of a collision bulkhead.

[CGD 73-96, 42 FR 49027, Sept. 26, 1977, as amended by CGD 81-101, 52 FR 7781, Mar. 12, 1987]

<sup>3</sup>See also §§ 32.56-5 and 32.60-10 of this chapter for limitations on the stowage of combustible liquids adjacent to ignition sources.